



MAGIDO®

X-51/HP SERIES

**INDUSTRIAL JET-SPRAY
PARTS WASHERS**



X-51/HP SERIES



X51/HP TECHNICAL SPECIFICATIONS

| Features | L-101HP | L-102HP | L-122HP |
|---------------------------------------|-------------------|---------------------|---------------------|
| ▶ Turntable with Containment Ring | 35" | 35" | 45" |
| ▶ Working Height | 19.5" | 19.5" | 27.5" |
| ▶ Jet-Spray Manifold (304 Stainless) | 1 | 2 | 2 |
| ▶ Vee-Jet Wash Nozzles (Optimized) | 22 | 44 | 58 |
| ▶ Load Weight | 440 lbs. | 440 lbs. | 770 lbs. |
| ▶ Tank Capacity | 46 gal | 46 gal | 74 gal |
| ▶ Pump: Lowara/Centrifugal GPM/PSI | (1) 2-HP 45/34 | (2) 1.5-HP 29/37 | (2) 2-HP 47.5/34 |
| ▶ High Pressure Spray Wand GPM/PSI | 3.7/870 | 3.7/870 | 3.7/870 |
| ▶ Tank Heater | 6kW | 6kW | 10kW |
| ▶ Max Operating Temperature | 160 F. | 160 F. | 160 F. |
| ▶ Pump Timer | 0-60 min | 0-60 min | 0-60 min |
| ▶ Voltage | 230/460 | 230/460 | 230/460 |
| ▶ Phase | 1-3 | 1-3 | 1-3 |
| ▶ Length (Lid Open) | 53" | 53" | 73" |
| ▶ Width | 51" | 51" | 73" |
| ▶ Height (Lid Open) | 78 ¾" | 78 ¾" | 85 ½" |
| ▶ Weight | 419 lbs. | 441 lbs. | 739 lbs. |

STANDARD FEATURES

- ▣ 304 Stainless Steel Cabinet
- ▣ 304 Stainless Steel Centrifugal Pump
- ▣ Stainless Steel Turntable with Containment Ring
- ▣ High Pressure Spray Wand
- ▣ Automatic Turntable Drive
- ▣ Incaloy Heating Elements
- ▣ Magnetic Float Fluid Level Sensor
- ▣ Strut Actuated Lid with Lock
- ▣ Viewing Window with Air Clearing Manifold
- ▣ LED Illuminated Cabinet
- ▣ Door Safety Switch
- ▣ Stainless Steel Bars
- ▣ Stainless Steel Vee-Jet Wash Nozzles
- ▣ Isolation Floor with Removable Chip Basket
- ▣ Removable Debris Screen
- ▣ Tank Drain

AVAILABLE OPTIONS

- ▣ Heated Dryer
- ▣ Fresh Water Rinse To Drain (X-51 Series)
- ▣ Air Blowoff Cycle
- ▣ Heated Dryer
- ▣ Filtration
- ▣ Oil Water Separator
- ▣ Oil Skimmer
- ▣ Steam/Mist Collector
- ▣ Automatic Water Fill
- ▣ 24/7 Programmable Heater Control
- ▣ Automatic Chemical Injector
- ▣ Removable Turntable With Cart
- ▣ Stack Light Tower
- ▣ Expanded Working Height
- ▣ Pump Upgrade

SAFETY FEATURES

- ▣ 24V Control Voltage
- ▣ NEMA 4 Electrical Panel
- ▣ Push Button Emergency Stop
- ▣ Rotary Main Power Disconnect Switch
- ▣ Safety Overload Protection
- ▣ Door Interlock Safety Switch
- ▣ Glove Box Interlock Safety Switch
- ▣ Locking Counter Balanced Lid
- ▣ Liquid Level Shutoff Switch
- ▣ High Limit Temperature Sensor
- ▣ No Sharp Metal Edges
- ▣ Low Noise Operation < 70 dBA
- ▣ CE Certified

